

# Semi – Circular Wash Fountain Stainless Steel

## Product Code WFSC

Stainless Steel Semi Circular Washfountain 965mm wide for 4 users. Available in adult height of 865mm or junior height of 659mm.

## Water Control Options

WFSC-H: Hand operation – Individual push buttons activate a time flow valve to supply water to their individual spray head for 5 to 60 seconds. This time may be pre-set at each individual valve.

WFSC-F: Foot operation – Individual foot valves activate the water supply to their individual spray head whilst the foot valve is depressed.

WFSC-SO: Sensor Operation – Individual Non-touch sensors activate the water supply to their individual spray head whilst the user's hands are in the bowl area.

## Fittings:

The washfountain is supplied fully assembled with the following fittings:  
Liquid soap dispensing system built into the stainless steel spray head assembly.  
Unslotted grated waste fitting with 38 OD x 100 mm long (1 1/2 OD x 4 in long)  
plain spigot tail piece.

## Water Supply and Pressure:

Hot and cold water supply pipes should be a minimum of 22 mm diameter before the TMV3 thermostatic mixing valve. For satisfactory operation a minimum 1.5 bar g. pressure is required for each supply where the water enters the washfountain pedestal. For pressures in excess of 7.0 bar g. a flow control reducing valve must be fitted.

## Water Consumption:

Each water outlet has a vandal resistant spray nozzle which provides a concentrated spray and is actuated by its own valve and individual user. Water consumption is limited to 1.9 litres per minute per spray nozzle.

## Options:

Adult or junior height  
TMV3 thermostatic mixing valve with isolating valve and test point.

