

Sluice Sink Wall Mounted

Model DU



Description:

The DU hospital pattern wall mounted disposal unit is manufactured as a fully pressed top from grade 304 stainless steel and includes a hopper with continuous flushing rim. The plain top is formed with a continuous anti-drip edge and turn down to all sides and is supplied with wall mounting brackets. Manufactured in accordance with the requirements of HTM64: Sanitary Assemblies (2006).

Size:

Overall size 600 x 600 mm

Disposal Hopper:

The slop hopper / sluice sink has a full continuous flushing rim to ensure efficient and hygienic cleansing.

Waste Outlet:

The sluice sink is manufactured with a 110 mm o/d plain vertical spigot outlet. A white polypropylene P or S trap can be supplied to convert the vertical spigot into a horizontal or vertical outlet

Flushing Inlet:

The sluice sink / slop hopper can be supplied as standard with a concealed back entry flushpipe connection for a duct mounted cistern, or with an exposed top entry connection for a surface mounted cistern.

Cistern and Flushpipe:

As an optional extra the sluice sink / slop hopper can be supplied with a plastic concealed cistern and flushpipe with through wall operating mechanism, or a stainless steel or plastic exposed cistern and flushpipe with lever operated flushing mechanism. To efficiently flush the sluice the recommended mounting height is 1450 mm minimum from the underside of the cistern to finished floor level.

Options:

Stainless steel front support legs.

Stainless steel hinged bucket grating.

WASHWARE ESSENTIALS LTD

Kestrel Court, Harbour Road, Portishead, Bristol BS20 7AN, Phone: 01275 390603

Web: www.washwareessentials.co.uk E-mail: enquiries@washwareessentials.co.uk